



AD-A130 488 UNSTEADY TRANSONIC PRESSURE MEASUREMENTS ON A SEMI-SPAN 1/2  
WIND TUNNEL MODEL. (U) NATIONAL AEROSPACE LAB AMSTERDAM

(NETHERLANDS) J J HORTSEN ET AL. MAR 83

UNCLASSIFIED NLR-TR-82069-U-PT-2 AFVAL-TR-83-3030-PT-2 F/G 20/A NL





MICROCOPY RESOLUTION TEST CHART  
NATIONAL BUREAU OF STANDARDS 196-A

AFWAL-TR-83-3039  
Part II

UNSTEADY TRANSONIC PRESSURE MEASUREMENTS ON A  
SEMI-SPAN WIND TUNNEL MODEL OF A TRANSPORT-  
TYPE SUPERCRITICAL WING (LANN MODEL)

PART II: PRESSURE DISTRIBUTIONS (PLOTTED) AND  
PLOTS OF THE VIBRATION MODES



J. J. Horsten  
R. G. den Boer  
R. J. Zwaan

National Aerospace Laboratory (NLR)  
Amsterdam, Netherlands

ADA130496

DATA FILE COP

Approved for public release; distribution unlimited

Copy available to DTIC does not  
permit fully legible reproduction

FLIGHT DYNAMICS LABORATORY  
AIR FORCE WRIGHT AERONAUTICAL LABORATORIES  
AIR FORCE SYSTEMS COMMAND  
WRIGHT-PATTERSON AIR FORCE BASE, OHIO 45433

2  
DTIC  
ELECTED  
S JUL 13 1983 D  
D

83 07 12 097

NOTICE

When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture use, or sell any patented invention that may in any way be related thereto.

This report has been reviewed by the Office of Public Affairs (ASD/PA) and is releasable to the National Technical Information Service (NTIS). At NTIS, it will be available to the general public, including foreign nations.

This technical report has been reviewed and is approved for publication.

Lawrence J. Huttell

LAWRENCE J. HUTTSELL  
Aerospace Engineer  
Aeroelastic Group

Fred A. Picchioni

FREDERICK A. PICCHIONI, Lt Col, USAF  
Chief, Analysis & Optimization Branch  
Structures & Dynamics Division

FOR THE COMMANDER

R. L. Kuster, Jr.

RALPH L. KUSTER, JR., Colonel, USAF  
Chief, Structures & Dynamics Division

"If your address has changed, if you wish to be removed from our mailing list, or if the addressee is no longer employed by your organization please notify AFWAL/FIBRC W-PAFB, OH 45433 to help us maintain a current mailing list".

Copies of this report should not be returned unless return is required by security considerations, contractual obligations, or notice on a specific document.

## **DISCLAIMER NOTICE**

**THIS DOCUMENT IS BEST QUALITY  
PRACTICABLE. THE COPY FURNISHED  
TO DTIC CONTAINED A SIGNIFICANT  
NUMBER OF PAGES WHICH DO NOT  
REPRODUCE LEGIBLY.**

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER AFWAL-TR-83- 3039, Part II	2. GOVT ACCESSION NO. <i>A130 488</i>	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) UNSTEADY TRANSONIC PRESSURE MEASUREMENTS ON A SEMI-SPAN WIND-TUNNEL MODEL OF A TRANSPORT-TYPE SUPERCRITICAL WING (LANN MODEL). Part II: Pressure Distributions (Plotted) and Plots of the Vibration Modes		5. TYPE OF REPORT & PERIOD COVERED Final Technical Report April 1980 - April 1982
7. AUTHOR(s) J. J. Horsten R. G. den Boer R. J. Zwaan	6. PERFORMING ORG. REPORT NUMBER NLR TR 82069 U Part II	
8. CONTRACT OR GRANT NUMBER(s) AFOSR Grant 80-0136		9. PERFORMING ORGANIZATION NAME AND ADDRESS National Aerospace Laboratory (NLR) Amsterdam, the Netherlands
10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS PE 61101F Project/Task/WU 2401/02/36		11. CONTROLLING OFFICE NAME AND ADDRESS Structures and Dynamics Division (FIB) Air Force Wright Aeronautical Laboratory Wright-Patterson Air Force Base, Ohio 45433
12. REPORT DATE March 1983		13. NUMBER OF PAGES 187
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)  Approved for Public Release; Distribution Unlimited		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Pressure Measurements Supercritical Wing Transonic Flow Unsteady Aerodynamics Wind-Tunnel Tests		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Unsteady transonic pressure measurements have been performed on a semi-span wind-tunnel model of a transport-type supercritical wing, oscillating in pitch. For each run, the vibration mode and detailed steady and unsteady pressure distributions have been measured. Sectional as well as wing aerodynamic coefficients have been obtained by integration of the pressure distributions. The tests covered a Mach number range between 0.62 and 0.95. The reduced frequency covered a range between zero and a maximum value varying from 0.3 at $M = 0.62$ to 0.2 at $M = 0.95$ (related to half mean aerodynamic chord).		

**Unclassified**

**SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)**

20. Cont'd

Part I of the report presents the general description, the aerodynamic coefficients (printed and plotted vs. incidence, reduced frequency and Mach number and the vibration modes.

Part II presents the plotted pressure distributions and vibration modes.

**Unclassified**

**SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)**

## FOREWORD

AFOSR Grant 80-0136, "Transonic Wind Tunnel Measurements on a Supercritical Wing" was initiated by the Structures and Dynamics Division (FIB) of the Air Force Wright Aeronautical Laboratories (AFWAL). The objective of this effort was to obtain experimental data on a supercritical wing to guide improvements in transonic unsteady aerodynamics.

This effort was a part of a cooperative program involving Lockheed-Georgia, Air Force, NASA, and NLR. This cooperative effort has become known as the LANN program.

The principal investigators at NLR were J. J. Horsten, R. G. den Boer, and R. J. Zwaan. The AFWAL project engineer was L. J. Huttell and the work unit was 24010236.

Part I of this report presents the general description, the aerodynamic coefficients (printed and plotted vs incidence, reduced frequency, and Mach number) and the vibration modes. Part II presents the plotted pressure distributions and vibration modes. The pressure distributions in tabulated form can be obtained from AFWAL/FIBRC upon request.

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/ _____	
Availability Codes	
Dist	Avail and/or Special
A	



## TABLE OF CONTENTS

	<u>PAGE</u>
Table 1 Steady Test Program for LANN Model . . . . .	1
Table 2 Unsteady Test Program for LANN Model . . . . .	2
Table 3 Test Program for Amplitude Variation and . . . . . Higher Harmonics	3
Table 4 Miscellaneous Runs for LANN Model . . . . .	4
Figure 1 Wing Planform . . . . .	5
Plotted Data (Run 15 through 258) . . . . .	6
APPENDIX A: Definitions and Sign Conventions . . . . .	176

## LIST OF SYMBOLS

Note: Coefficients derived from the zeroth harmonic component of unsteady pressure signals, are indicated simply as "steady" coefficients instead of "mean" coefficients. For a pure sinusoidal signal, there is principally no difference between steady and mean coefficients.

$a$	modulus of pressure tube transfer function, $a = \text{mod}(p_u/p_i)$ (see section 3.1 and figure 6 in part I)
AR	aspect ratio, AR = 7.92
AC	aerodynamic center
$c$	local chord, m
$c_{AC}$	mean aerodynamic chord, $c_{AC} = 0.268$ m
$c_r$	root chord, m
$c_t$	tip chord, m
$C_m$	steady sectional pitching moment coefficient (see App. A)
$C_{mi}$	unsteady sectional pitching moment coefficient, $C_{mi} = C_m' + i C_m''$ (see App. A)
$C_{mq}$	quasi-steady sectional pitching moment coefficient (see App. A)
$C_M$	steady wing pitching moment coefficient (see App. A)
$C_{Mi}$	unsteady wing pitching moment coefficient (see App. A)
$C_{Mq}$	quasi-steady wing pitching moment coefficient (see App. A)
$C_{pi}$	unsteady pressure coefficient, $C_{pi} = C_p' + i C_p''$ (see App. A)
$C_{piT}$	value of $C_{pi}$ measured with in situ transducer, $C_{piT} = p_i / q_\infty \alpha_i = C_{pT}' + i C_{pT}''$
$C_{pm}$	steady pressure coefficient (see App. A)
$C_{pq}$	quasi-steady pressure coefficient (see App. A)
$C_z$	steady sectional normal force coefficient (see App. A)
$C_{zi}$	unsteady sectional normal force coefficient, $C_{zi} = C_z' + i C_z''$ (see App. A)
$C_{zq}$	quasi-steady sectional normal force coefficient (see App. A)
$C_Z$	steady wing normal force coefficient (see App. A)
$C_{Zi}$	unsteady wing normal force coefficient, $C_{Zi} = C_z' + i C_z''$ (see App. A)
$C_{Zq}$	quasi-steady wing normal force coefficient (see App. A)

DZ	ratio of acceleration pick-up signal and LVDT displacement signal, $DZ = DZ' + i DZ''$
$DZ_1$	amplitude of LVDT displacement, mm
f, FREQ	frequency, Hz
harm, HARM	harmonic component (harm = 0: mean, harm = 1: 1st harmonic, harm = 2: 2nd harmonic)
i	$\sqrt{-1}$
k, REDFR.	reduced frequency, $k = \pi f c_{AC}/V$
M, Mach, MACH	free stream Mach number
M	steady sectional pitching moment about quarter-chord, Nm/m (see App. A)
$M_i$	unsteady sectional pitching moment about quarter-chord, Nm/m/rad (see App. A)
$M_{i\_wing}$	unsteady wing pitching moment about aerodynamic center, Nm/rad (see App. A)
M-LOC	local Mach number
$M_q$	quasi-steady sectional pitching moment about quarter-chord, Nm/m/rad (see App. A)
$M_{q\_wing}$	quasi-steady wing pitching moment about aerodynamic center, Nm/rad (see App. A)
$M_{wing}$	steady wing pitching moment about aerodynamic center, Nm (see App. A)
$N_m$	number of acceleration pick-ups, $N_m = 12$
$N_p$	number of pressure tubes at each section, $N_p = 40$
$N_s$	number of sections, $N_s = 6$
$N_T$	number of transducers, $N_T = 12$
p	pressure at model surface, $p = p_m + p_i$ , Pa
p, P-SETTL.	stagnation pressure, Pa
$p_i$	nth harmonic component of unsteady pressure at model surface, $p_i =  p_i  \exp[i(\omega t)]$ , Pa (see Fig. 6 in part I)
$p_{i_T}$	value of $p_i$ measured with in-situ transducer
$p_m$	mean pressure, Pa
$p_q$	amplitude of quasi-steady pressure oscillation, $p_q = [p_m(\alpha_m + \Delta\alpha) - p_m(\alpha_m - \Delta\alpha)]/2$ , Pa
$p_u$	nth harmonic component of unsteady pressure at the end of a pressure tube, $p_u =  p_u  \exp[i(\omega t + \phi)]$ , Pa (see Fig. 6 in part I)
$q_\infty, Q$	free-stream dynamic pressure, Pa

$Re$ , $RE$	Reynolds number, $Re = Vc_{AC}/\nu$
$s$	semi-span, $s = 1.000 \text{ m}$
$S$	wing surface, $S = 0.2526 \text{ m}^2$
$t$	airfoil thickness, $\text{m}$
$t$	time, $\text{s}$
$T$	model temperature, deg cent.
T-SETTL.	stagnation temperature, deg cent.
$V$	free-stream velocity, $\text{m/s}$
WRP	Wing Reference Plane (see Fig. 1) ( $X$ - $y$ plane)
$x$	$x = X - X_{\text{leading}}$
$x_{tr}$	$x$ -coordinate of boundary layer transition strip
$X$	coordinate in free-stream direction, $\text{m}$ (see Fig. 1)
$X_r$	$X$ -coordinate of rotation axis, $\text{m}$ (see Fig. 1)
$y$	spanwise coordinate, $\text{m}$ (see Fig. 1)
$z$	coordinate normal to the $X$ - $y$ plane, $\text{m}$
$Z$	steady sectional normal force, $\text{N/m}$ (see App. A)
$Z_i$	unsteady sectional normal force, $\text{N/m/rad}$ (see App. A)
$Z_{i\_wing}$	unsteady wing normal force, $\text{N/rad}$ (see App. A)
$Z_q$	quasi-steady sectional normal force, $\text{N/m/rad}$ (see App. A)
$Z_{q\_wing}$	quasi-steady wing normal force, $\text{N/rad}$ (see App. A)
$Z_{wing}$	steady wing normal force, $\text{N}$ (see App. A)
$\alpha$ , alpha, ALFA	wing incidence at LVDT position, $\alpha = \alpha_m + \alpha_i$ , deg
$\alpha_i$	unsteady wing incidence at LVDT position, $\alpha_i =  \alpha_i  \exp(i\omega t) = \Delta\alpha \exp(i\omega t)$ , deg
$\alpha_m$	steady wing incidence at LVDT position, deg
$\Delta\alpha$ , $\Delta\alpha_{\text{DALPHA}}$ , DALPHA	amplitude of unsteady wing incidence at LVDT position $\Delta\alpha =  \alpha_i $ , deg
$\varphi$	phase of tube transfer function, $\varphi = \arg(p_u/p_i)$
$n$	relative spanwise coordinate, $n = y/s$
$\Lambda_{0.25}$	sweep angle of quarter chord line, deg
$\nu$	kinematic viscosity ( $\text{m}^2/\text{s}$ )
$\omega$	angular velocity, $\omega = 2\pi f$ , rad/s
$\theta$	local wing incidence, deg (see Fig. 1)
$\Omega$	wing twist, $\Omega = \theta_t - \theta_r$ , deg (see Fig. 1)

$+$  upper  $z < 0$  (see Fig. 1)  
 $-$  lower  $z > 0$  (see Fig. 1)  
 $\infty$  free-stream

x

TABLE 1  
Steady test program for LANN model (run numbers)

$\alpha \backslash M$	0.62	0.72	0.77	0.82	0.87	0.95
-0.4	16	27	46	67	88	97
0.35	17			68		
0.60*)	15/19	28	47	69	89	98
0.85	18			70		
1.60	20	29	48	71	90	99
2.00	183			218		
2.35	235	238	240	132		155
2.50				219		
2.60*)	234	109	121	222/133		154
2.75				220	242	245
2.85	236	237	241	134		156
2.90				231		230
3.00*)	184			221	168	246
3.25				223	244	247
3.50				224		
3.60	104/232	110	122	135		157
4.00				225	169	248
4.50				226		
4.75			201	205		
5.00*)	185	193	202	206		228
5.25			203	207		
5.50				227		
6.00	186	194	204	208		229

\*) Steady incidences for which unsteady measurements were performed as well

TABLE 2  
Unsteady test program for LANN model (run numbers)

f		12	24	36	48	60	72
$\Delta\alpha$		1.0	0.25	0.25	0.25	0.25	.025
$\alpha$	M						
0.6	0.62	36	129/22	23	24	25	26
	0.72		30		31	32	33
	0.77	117	118	119	120	65	66
	0.82	83	73	77	85	86	87
	0.87	91	92	93	94	95	96
	0.95		100		101	102	103
2.6	0.62		105		106	107	108
	0.72	111	112	113	114	115	116
	0.77	123	124	125	126	128	
	0.82	139	143	150	151	152	153
3.0	0.72		165				
	0.77		166				
	0.82		167				
	0.87		170		171	172	173
	0.95	250	175	179	180	181	182
5.0	0.62	187	188	189	190	191	192
	0.72	195	196	197	198	199	200
	0.82	211	212	214	215	216	217

TABLE 3  
 Test program for amplitude variation and higher harmonics  
 for LANN model (run numbers)

M	$\alpha$	f	$\Delta\alpha$ harm	0.125	0.25	0.5	1.0
0.62	0.6	12	1	34	21	35	36
		24	1	37	22/39/129	42	
		24	2		40/130	43	
		24	3		41/131	44	
		36	1	45	23		
0.82	0.6	12	1		72	82	83
		24	1	78	73	79	
		24	2		74	80	
		24	3		75	81	
		36	1	76	77		
0.82	2.6	12	1	136	137	138	139
		24	1	140	143	146	
		24	2	141	144	147	
		24	3	142	145	148	
		36	1	149	150		
0.95	2.6	12	1		161	162	163
0.95	3.0	24	1		175	178	
		24	2		176		
		24	3		177		
0.82	5.0	12	1		209	210	211
		24	1		212	213	

TABLE 4  
Miscellaneous runs for LANN-model

run number	$\alpha$	M	f	$\Delta\alpha$	harm
38	0.6	0.62	24.0	0.50	1
84	0.6	0.82	18.0	0.50	1
127	2.6	0.77	50.0	0.25	1
164	3.0	0.95	12.0	0.50	1
174	3.0	0.95	12.0	0.50	1
158	0.6	0.95	30.1	0.05	1
159	0.6	0.95	30.1	0.05	2
160	0.6	0.95	30.1	0.05	3
253	4.0	0.00	12.0	0.25	1
254	4.0	0.00	24.0	0.25	1
255	4.0	0.00	36.0	0.25	1
256	4.0	0.00	48.0	0.25	1
257	4.0	0.00	60.0	0.25	1
258	4.0	0.00	72.0	0.25	1













Fig. 1 Wing planform (dimensions in mm)





























































Date	- 14-12-1981	Tubes
Runnr.	= .39	△ Upper stat, real
Mach	= .623	◆ Upper imag
Freq.	= 24.0 Hz	- Lower side
Redfr.	= .098	Transducers
Alpha	= .594 Degr.	△ Upper real
Dalpha	= .249 Degr.	◆ Upper imag
Harm	= 1	


-LANN-


-LANN-








































Date - 15-12-1981

Bumper 3 72

Mach = .821

Freq. = 12.0 Hz  
Bdfr = 838

Refr. = .038  
Alpha = .596 Degr

$\Delta\alpha = .261$  Degr

Harr - 1

**ANSWER**

47/6647

卷之三

— 1 —

## Tubes

- Upper stat, real
- Upper impo

- Upper way
- Lower side

## Transducers A Upper seal

△ Upper real  
▼ Upper imag

-100-



-LHNN-


[View all posts by \[Author Name\]](#) [View all posts in \[Category\]](#)


UIN-MITTE


*July 1972*

-LANN-














Date - 16-12-1981      Tubes  
 Runnr. = .75      ▲ Upper stat,real  
 Mach = .821      ▽ Upper imag  
 Freq. = 24.0 Hz      \* Lower side  
 Redfr. = .076      △ Transducers  
 Alpha = .593 Degr.      □ Upper real  
 Dalpha = .260 Degr.      ▽ Upper imag  
 Harm = 3


-LANN-































Date - 15-12-1981      Tubes  
 Runnr. = 84      ▲ Upper stat,real  
 Mach = .821      ▽ Upper imag  
 Freq. = 18.0 Hz      × Lower side  
 Redfr. = .057      ▲ Transducers  
 Alpha = .594 Degr.      ▽ Upper real  
 Dalpha = .495 Degr.      ▽ Upper imag  
 Harn = 1




-LANN-



























































































Date - 15-12-1981 Tubes  
 Runnr. = 117 ▲ Upper stat,real  
 Mach = .774 ▽ Upper imag  
 Freq. = 12.0 Hz + Lower side  
 Redfr. = .040 Transducers  
 Alpha = .601 Degr. ▲ Upper real  
 Dalpha = 1.006 Degr. ▽ Upper imag  
 Harm = 1



-LANN-





























AD-A130 488 UNSTEADY TRANSONIC PRESSURE MEASUREMENTS ON A SEMI-SPAN 2/2  
WIND TUNNEL MODEL. (U) NATIONAL AEROSPACE LAB AMSTERDAM  
(NETHERLANDS) J. J. HORTSEN ET AL. MAR 83  
UNCLASSIFIED NLR-TR-82069-U-PT-2 AFWAL-TR-83-3030-PT-2 F/G 20/4 NL


END  
DATE FILMED  
8-83  
DTIC







MICROCOPY RESOLUTION TEST CHART  
NATIONAL BUREAU OF STANDARDS 1967 A


































Date - 16-12-1981      Tubes  
 Runn. = 140      ▲ Upper stat, real  
 Mach = .922      ▽ Upper imag  
 Freq. = 24.0 Hz      ● Lower side  
 Redfr. = .875      ▲ Transducers  
 Alpha = 2.599 Degr.      ▽ Upper real  
 Dalpha = .125 Degr.      △ Upper imag  
 Hars = 1


-LANN-



























































































Date = 16-12-1981      Tubes  
 Runnr. = 171      ▲ Upper stat,real  
 Mach = .970      ▽ Upper imag  
 Freq. = 48.0 Hz      ◆ Lower side  
 Redfr. = .143      ▲ Upper real  
 Alpha = 3.000 Degr.      ▽ Upper imag  
 Dalpha = .261 Degr.  
 Harm = 1


-LANN-






























































Date - 16-12-1981      Tubes  
 Runnr. = 192      ▲ Upper stat, real  
 Mach = .622      ▽ Upper imag  
 Freq. = 72.0 Hz      • Lower side  
 Redfr. = .294      ▲ Upper real  
 Alpha = 5.000 Degr.      ▽ Upper imag  
 Dalpha = .250 Degr.      Hars = 1

-LANN-












Date = 16-12-1981      Tubes  
 Runnr. = 195      ▲ Upper stat,real  
 Mach = .721      ▽ Upper imag  
 Freq. = 12.0 Hz      • Lower side  
 Redfr. = .043      ▲ Transducers  
 Alpha = 4.997 Degr.      △ Upper real  
 Dalpha = .998 Degr.      ▽ Upper imag  
 Harm = 1


-LANN-













































































































Date = 17-12-1981 Tubes  
 Runnr. = 253 ▲ Upper stat,real  
 Mach = .021 ▽ Upper imag  
 Freq. = 12.0 Hz • Lower side  
 Redfr. = 1.348 Transducers  
 Alpha = 3.995 Degr. ▲ Upper real  
 Dalpha = 1.000 Degr. ▽ Upper imag  
 Harm = 1 -LANN-




Date = 17-12-1981 Tubes  
 Runnr. = 254 ▲ Upper stat,real  
 Mach = .021 ▽ Upper imag  
 Freq. = 24.0 Hz • Lower side  
 Redfr. = 2.681 Transducers  
 Alpha = 4.005 Degr. ▲ Upper real  
 Dalpha = .250 Degr. ▽ Upper imag  
 Harm = 1 -LANN-



Date = 17-12-1981 Tubes  
 Runnr. = 255 ▲ Upper stat,real  
 Mach = .030 ▽ Upper imag  
 Freq. = 36.0 Hz • Lower side  
 Redfr. = 2.843 Transducers  
 Alpha = 3.993 Degr. ▲ Upper real  
 Dalpha = .252 Degr. ▽ Upper imag  
 Harm = 1 -LANN-




Date = 17-12-1981 Tubes  
 Runnr. = 256 ▲ Upper stat,real  
 Mach = 0.000 ▽ Upper imag  
 Freq. = 48.0 Hz • Lower side  
 Redfr. = \$\$\$\$\$ Transducers  
 Alpha = 3.990 Degr. ▲ Upper real  
 Dalpha = .250 Degr. ▽ Upper imag  
 Harm = 1 -LANN-




Date = 17-12-1981      Tubes  
 Runnr. = 257      ▲ Upper stat,real  
 Mach = .821      ▽ Upper imag  
 Freq. = 60.0 Hz      ■ Lower side  
 Redfr. = 6.782      Transducers  
 Alpha = 3.983 Degr.      ▲ Upper real  
 Dalpha = .251 Degr.      ▽ Upper imag  
 Harm = 1

-LANN-




Date = 17-12-1981      Tubes  
 Runnr. = 258      ▲ Upper stat,real  
 Mach = 0.000      ▽ Upper imag  
 Freq. = 72.0 Hz      ■ Lower side  
 Redfr. = 38888      Transducers  
 Alpha = 3.972 Degr.      ▲ Upper real  
 Dalpha = .246 Degr.      ▽ Upper imag  
 Harm = 1

-LANN-



APPENDIX A  
Definitions and sign conventions



Note: Coefficients derived from the zeroth harmonic component of unsteady pressure signals, are indicated simply as "steady" coefficients instead of "mean" coefficients. For a pure sinusoidal signal, there is principally no difference between steady and mean coefficients.

Steady

Steady pressure coefficient:

$$C_{pm} = \frac{p_m - p_\infty}{q_\infty}$$

Steady sectional normal force:

$$Z = C_z q_\infty \cdot c ; C_z = - \int_0^1 (C_{pm+} - C_{pm-}) d\left(\frac{x}{c}\right)$$

Steady sectional pitching moment about quarter-chord

$$M = C_m q_\infty \cdot c^2 ; C_m = - \int_0^1 (C_{pm+} - C_{pm-}) \left(\frac{x}{c} - 0.25\right) d\left(\frac{x}{c}\right)$$

Steady wing normal force:

$$Z_{\text{wing}} = C_Z \cdot q_\infty \cdot S ; C_Z = - \frac{1}{S} \int_0^{\frac{S}{c}} \int_0^1 (C_{p\infty+} - C_{p\infty-}) d\left(\frac{x}{c}\right) \cdot c \cdot dy$$

Steady wing pitching moment about aerodynamic centre:

$$M_{\text{wing}} = C_M \cdot q_\infty \cdot c_{AC} \cdot S ; C_M = - \frac{1}{Sc_{AC}} \int_0^{\frac{S}{c}} \int_0^1 (C_{p\infty+} - C_{p\infty-}) \left( \frac{x-x_{AC}}{c} \right) d\left(\frac{x}{c}\right) c^2 \cdot dy$$

### Unsteady

Unsteady pressure coefficient:

$$C_{pi} = C'_p + i \cdot C''_p = \frac{p_i}{q_\infty \cdot a_i}$$

Unsteady sectional normal force:

$$Z_i = 2\pi \cdot q_\infty \cdot \frac{c}{2} \cdot C_{zi} \cdot \Delta\alpha \cdot e^{i\omega t}$$

$$C_{zi} = C_z + i \cdot C'_z = - \frac{1}{\pi} \int_0^1 (C_{pi+} - C_{pi-}) d\left(\frac{x}{c}\right)$$

Unsteady sectional pitching moment about quarter-chord:

$$M_i = 2\pi \cdot q_\infty \cdot \left(\frac{c}{2}\right)^2 \cdot C_{mi} \cdot \Delta\alpha \cdot e^{i\omega t} ;$$

$$C_{mi} = C_m + i \cdot C'_m = - \frac{2}{\pi} \int_0^1 (C_{pi+} - C_{pi-}) \left( \frac{x}{c} - 0.25 \right) d\left(\frac{x}{c}\right)$$

Unsteady wing normal force:

$$Z_{i\text{wing}} = 2\pi \cdot q_\infty \cdot \frac{S}{2} \cdot C_{zi} \cdot \Delta\alpha \cdot e^{i\omega t} ;$$

$$C_{zi} = C'_z + i \cdot C''_z = - \frac{1}{\pi S} \int_0^{\frac{S}{c}} \int_0^1 (C_{pi+} - C_{pi-}) d\left(\frac{x}{c}\right) \cdot c \cdot dy$$

Unsteady wing pitching moment about aerodynamic centre:

$$M_{i\text{wing}} = 2\pi \cdot q_\infty \cdot \left(\frac{c_{AC}}{2}\right) \cdot \frac{S}{2} \cdot C_{mi} \cdot \Delta\alpha \cdot e^{i\omega t} ;$$

$$C_{mi} = C'_m + i \cdot C''_m = - \frac{2}{\pi Sc_{AC}} \int_0^{\frac{S}{c}} \int_0^1 (C_{pi+} - C_{pi-}) \left( \frac{x-x_{AC}}{c} \right) d\left(\frac{x}{c}\right) c^2 \cdot dy$$

### Quasi-steady

Quasi-steady pressure coefficient:

$$C_{pq} = \frac{p_q}{q_\infty \Delta \alpha}$$

Quasi-steady sectional normal force:

$$Z_q = 2\pi \cdot q_\infty \cdot \frac{c}{2} C_{Zq} \cdot \Delta \alpha ;$$

$$C_{Zq} = \frac{1}{\pi} \cdot \frac{C_Z(\alpha_m + \Delta \alpha) - C_Z(\alpha_m - \Delta \alpha)}{2\Delta \alpha}$$

Quasi-steady sectional pitching moment about quarter-chord:

$$M_q = 2\pi \cdot q_\infty \cdot \left(\frac{c}{2}\right)^2 C_{Mq} \cdot \Delta \alpha ;$$

$$C_{Mq} = \frac{2}{\pi} \cdot \frac{C_m(\alpha_m + \Delta \alpha) - C_m(\alpha_m - \Delta \alpha)}{2\Delta \alpha}$$

Quasi-steady wing normal force:

$$Z_{q\_wing} = 2\pi \cdot q_\infty \cdot \frac{S}{2} C_{Zq} \cdot \Delta \alpha ;$$

$$C_{Zq} = \frac{1}{\pi} \cdot \frac{C_Z(\alpha_m + \Delta \alpha) - C_Z(\alpha_m - \Delta \alpha)}{2\Delta \alpha}$$

Quasi-steady wing pitching moment about aerodynamic centre:

$$M_{q\_wing} = 2\pi \cdot q_\infty \cdot \left(\frac{c_{AC}}{2}\right) \cdot \frac{S}{2} C_{Mq} \cdot \Delta \alpha ;$$

$$C_{Mq} = \frac{2}{\pi} \cdot \frac{C_M(\alpha_m + \Delta \alpha) - C_M(\alpha_m - \Delta \alpha)}{2\Delta \alpha}$$

.0 .2 .4 .6 .8 x/c

.0 .2 .4 .6 .8 x/c .0 .2 .4 .6 .8 x/c .0 .2 .4

165

END  
DATE  
FILMED

8 - 8

DTIC